

MCVC3L

REDUCED 3 VOLTAGES WEDGE MEASUREMENT



DESCRIPTION

FEATURES

CONFIGURATION

- Integrated flash lamp
- Remote flash lamp

INPUT 1 - voltage

- Threshold 50mV
- Threshold 150mV
- Threshold 300mV
- Specific Threshold in mV

OTHER FEATURES

- Alarms :
 - Sound Alarm : Buzzer 96dB (IP67)
 - Visual Alarm : xenon beacon (60 flashes / min ; 5.0J (IP65))

OPTION

- Selftest push button : validates trigger levels and lights and sounds signals.
- 3 green LEDs, 3 red LEDs, beacon and buzzer

OPTION 1

- No option 1
- #### OPTION 2
- Connecting wires
 - No option 2

POWER SUPPLY

- 110Vac (45 to 65Hz / 18VA max.)
- 230Vac (45 to 65Hz / 18VA max.)
- 24Vdc +-10%
- 12Vdc +-10%

GALVANIC ISOLATION

- > 3500 Vrms for : IN / AUX. SUPPLY

TEMPERATURE RANGE

- -25 to 70°C

TEMPERATURE OF CALIBRATION

- 20 to 25°C

MAGNETIC FIELDS

- up to 150 Gauss in X, Y, Z dimensions



PRICE On quote only

WEB LINK [Click here](#)

SECTOR ALUMINIUM & ALKALI
ELECTROLYSIS
ALUMINIUM MAINTENANCE

USAGE

WEIGHT 1.3 Kg

LENGTH 235 mm

WIDTH 193 mm

HEIGHT 88 mm

CUSTOMS CODE

C. OF ORIGIN France

GUARANTEE 1 year

CERTIFICATION CE

CONTACT commercial@serem-electronics.com

MCVC3L

REDUCED 3 VOLTAGES WEDGE MEASUREMENT



CASING

- Polycarbonate enclosure with transparent lid
- junctions via 1.5mm² input / supply wires