

PERMA

PERMEAMETER



DESCRIPTION

The Permeameter is a permeability test bench for cathode carbon rods.

FEATURES

CONFIGURATION

- Pressure : 0 - 1 Bar, accuracy: 0.2% FS,
- Air flow : 0 - 1 L/min, accuracy: 0.1% FS,
- Air temperature : 0 - 50°C, accuracy: 1% FS,
- Permeability calculated : 0.1 - 25Nperm

INPUT 2 - configuration

- Support sample : diameter 50mm, height 100mm
- Support sample : diameter 50mm, height 50mm

OTHER FEATURES

- Test limits : Max.pressure loss: 1 bar, Max. flow: 1 l/min

OPTION

- 1 tube / Latex membrane furnished

OPTION 2


- 2nd support sample
- No option 2

POWER SUPPLY

- Electrical : 115Vac, 50-60Hz
- Air pressure : 4 bar minimum
- Electrical : 230Vac, 50-60Hz
- Air pressure : 4 bar minimum

CASING

- 1 Panel PC with 17" touch screen for management of process,
- 3 USB sockets (including one on front side),
- 1 Ethernet Plug,
- 1 Main cut-out switch,
- 1 luminous start button,
- 1 button to start again in order to facilitate the installation of the sample,
- 1 button for ejection by air of sample in place,
- 1 reset button for emergency stop,
- 1 sample support 50mm equipped with its protection cover



PRICE On quote only

WEB LINK [Click here](#)

SECTOR ALUMINIUM CHLOR ALKALI

USAGE ELECTROLYSIS
ALUMINIUM LABORATORY

WEIGHT 50 kilogramme

LENGTH

WIDTH

HEIGHT

CUSTOMS CODE 90 30 89 00

C. OF ORIGIN France

GUARANTEE 1 year

CERTIFICATION CE

CONTACT commercial@serem-electronics.com