

## CAFD

## CONTROL CABINET



### DESCRIPTION

This device is used to monitor and / or replace the orders from the potmicros to the "crustbreaker" and "feeder" 24Vcc solenoid valves.

### FEATURES

#### CONFIGURATION

- Control by 115Vdc
- Control by 24Vdc

#### POWER SUPPLY

- Built-in 12V / 4Ah Ni-Mh battery and charger, 1h non stop autonomy standard 100-240Vac 50/60Hz power supply for the built-in charger.

#### CASING

- Insulated casing with transport handle, protected against short-circuits at output.

Control switches :

- double pole for Monitoring / Control
- momentary double-pole for Crustbreaker / O / Feeder

Monitoring lights :

- red for Feeder
- green for Crustbreaker

Function lights :

- red "neon" for charging
- green LED for battery use
- orange LED for 24Vcc at output during control

Junctions :

- with Crustbreaker / Feeder : 4pins female socket
- with cord to potmicro : 3pins male socket
- with power supply : 3pins male socket

**PRICE** On quote only

**WEB LINK** [Click here](#)

**SECTOR**

**USAGE**

**WEIGHT** 3.5 Kg

**LENGTH** 330 mm

**WIDTH** 195 mm

**HEIGHT** 120 mm

**CUSTOMS CODE** 90 32 90 00 10

**C. OF ORIGIN** France

**GUARANTEE** 1 year

**CERTIFICATION** CE

**CONTACT** [commercial@serem-electronics.com](mailto:commercial@serem-electronics.com)